

55/2W-22CB

STATE OF OREGON  
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES  
1069 State Office Building, Portland 1, Oregon

RECEIVED - PTLD

FEB 27 1985

MARI  
53582

WELL SUMMARY REPORT  
(Submit in duplicate)

DEPT. OF GEOLOGY  
& MINERAL INDUS

Operator Oregon Natural Gas Dev. Corp. Field St. Louis  
Well No. DeShazer #13-22 Sec. 22, T. 5S, R. 2W, W. B. & M.  
Location 1860.22' N and 560.3' E of SW corner Elevation above sea level 193.21' feet

All depth measurements taken from top of Kelly Bushing, which is 11.1 feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date February 26, 1985 Signed Charles Stinson  
Charles Stinson W. W. Lipscomb Title Vice President-Operations  
Engineer or Geologist Superintendent (President, Secretary or Agent)

Commenced drilling 2/7/85 Completed drilling 2/19/85 Drilling tools ~~API~~ Rotary  
Total depth 2511' Plugged depth \_\_\_\_\_ GEOLOGICAL MARKERS DEPTH  
Junk None Columbia River Basalt 1275-1770  
Eugene Formation 1770-2200  
Spencer Formation 2200-TD

Commenced producing Never produced Date \_\_\_\_\_ Flowing/gas lift/pumping (cross out unnecessary words)

Initial production  
Production after 30 days

Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure

CASING RECORD (Present Hole)

Size of casing (A.P.L.)	Depth of shoe	Top of casing	Weight of casing	New or second hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cementing if through perforations
8-5/8"	506'	surf.	24.0#	New	Smls	K-55	12-1/4"	290	N/A

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				